


Stehleuchten | 220-240 V | 1 topLED 33 W DC 900 mA

CRI 90

8910



Technische Daten	
Jahr der Verwirklichung	2019
Typ	Stehleuchten
Installationsposition	Boden
Installationsumgebung	Indoor
Lichtquelle	LED
Optik	General Lighting
Light emission direction	upward
Lampenleistung	33 W
Lichtstrom (Lichtquelle)	3587 lm
Frequency	60 - 50 Hz
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	1
IP	IP20
IP optisches System	IP40
Glühdrahtprüfung	650°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	PUSH DIM
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	4 m
Steckdose	Type C
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Nettogewicht	8.74 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Gehäuse	
Material	PC
Farbe	transparent
Bearbeitungstyp	Sandstrahlen

Oberfläche Diffusor	
Material	PMMA
Farbe	transparent
Bearbeitungstyp	Siebdruck

Oberfläche sockel	
Material	Eisen
Farbe	Weiß geprägt RAL 9003
Bearbeitungstyp	Pulverbeschichtung

Stehleuchten | 220-240 V | 1 topLED 33 W DC 900 mA | CRI 90
8910

Single emission floor lamp for indoor application. The warm white LED light source with a general lighting light distribution is composed of 1 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 3587 lm, with a 108.7 lm/W nominal luminous efficacy.

The device body is made of PC and features a transparent finish, processed by means of sandblasting; the diffuser is made of pmma with a silk-screening treatment. The ingress protection degree is IP20; the total weight is of 8.74 kg.

The total absorbed power is W. The power supply cable is included and features a 4 m lenght.

The device features protection class I and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Eigenschaften	
Lichtstrom (Lichtquelle)	3587 lm
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Verbindungstemperatur (Leuchte)	80
Standardumgebungstemperatur	25
LED Life / Failure Ratio	
L80 B20 C0 61000h (at Tj 105 Ta 25)	