


Stehleuchten | 220-240 V | 1 topLED 33 W DC 900 mA

CRI 90

8911



Technische Daten	
Jahr der Verwirklichung	2019
Typ	Stehleuchten
Installationsposition	Boden
Installationsumgebung	Indoor
Lichtquelle	LED
Optik	General Lighting
Light emission direction	upward
Lampenleistung	33 W
Lichtstrom (Lichtquelle)	3587 lm
Frequency	60 - 50 Hz
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	1
IP	IP20
IP optisches System	IP40
Glühdrahtprüfung	650°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	PUSH DIM
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	4 m
Steckdose	Type C
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Nettogewicht	8.74 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Gehäuse	
Material	PC
Farbe	transparent
Bearbeitungstyp	Sandstrahlen

Oberfläche Diffusor	
Material	Polymethylmethacrylat UV-beständige
Bearbeitungstyp	Siebdruck

Oberfläche sockel	
Material	Eisen
Farbe	Weiß geprägtem RAL 9003
Bearbeitungstyp	Pulverbeschichtung

Stehleuchten | 220-240 V | 1 topLED 33 W DC 900 mA | CRI 90
8911

Single emission floor lamp for indoor application. The warm white LED light source with a general lighting light distribution is composed of 1 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 3587 lm, with a 108.7 lm/W nominal luminous efficacy.

The device body is made of PC and features a transparent finish, processed by means of sandblasting; the diffuser is made of uv resistant polymethylmethacrylate with a silk-screening treatment. The ingress protection degree is IP20; the total weight is of 8.74 kg.

The total absorbed power is W. The power supply cable is included and features a 4 m lenght.

The device features protection class I and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Eigenschaften	
Lichtstrom (Lichtquelle)	3587 lm
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Verbindungstemperatur (Leuchte)	80
Standardumgebungstemperatur	25
LED Life / Failure Ratio	
L80 B20 C0 61000h (at Tj 105 Ta 25)	